

LONG KE DEFENSE

LKD. 32D SPECIFICATION

Model Number Φ 32.0mm	Maximum Allowable Voltage		Varistor Voltage		Clamping voltage (max.)		Rated voltage	Maximum Peak Current (8/20μs)		Maximum Energy (Joule)	Typical Capacitance (Reference)
	AC. Rms	DC	V1.0mA (V)		VC	IP	reference	In.10 times	I Max.	10/1000	@ 1KHz
	(V)	(V)	min.	max.	(V)	(A)	(V)	(KA)		μs	(pf)
32D201K	130	170	185	225	340	200	AC 125	15	30	250	5200
32D221K	140	180	198	242	360	200				270	4500
32D241K	150	200	216	264	395	200				290	5100
32D271K	175	225	243	297	455	200				300	4800
32D301K	190	250	270	330	500	100				330	4500
32D331K	210	275	297	363	550	200	AC 250			360	4300
32D361K	230	300	324	396	595	200	Telephone			380	3900
32D391K	250	320	351	429	650	200	test			400	3200
32D431K	275	350	387	473	710	200	AC 250			430	3100
32D471K	300	385	423	517	775	200				460	2800
32D511K	320	415	459	561	845	200				510	2700
32D561K	350	460	504	616	925	200				540	1775
32D621K	385	505	558	682	1025	200				570	2400
32D681K	420	560	612	748	1120	200				600	2200
32D711K	440	585	644	786	1180	200				610	2100
32D751K	460	615	675	825	1240	200				620	2000
32D781K	485	640	702	858	1290	200				660	1900
32D821K	510	670	738	902	1355	200	AC 380 or G			700	1800
32D911K	550	745	819	1001	1500	200				750	1300
32D951K	575	765	855	1045	1570	200				780	1200
32D102K	625	825	900	1100	1650	200				810	1100
32D112K	680	895	990	1210	1815	200				910	1000
32D122K	750	990	1080	1320	1980	200				960	920